


Joliet Electric Motors

is committed to delivering integrated motor solutions to existing rig fleets and new builds. We focus on proven solutions that improve operational efficiency.



RATINGS:

Maximum Continuous Power: 1230HP (918 KW), 8080 lb-ft., 1170 Amps, 600 - 690 VAC, 800 RPM
Constant Output Speed: 800 – 1400 RPM

Intermittent Duty Cycle: 1845HP (1376 KW), 12120 lb-ft., 1755 Amps, 600 - 690 VAC, 800 RPM
Duty Cycle: 60 sec. ON, 120 sec. OFF Constant Output Speed: 800 - 925 RPM

Max RPM: 3000
Ambient Temp.: -40° to +55°

FEATURES & SPECIFICATIONS:

- Form Wound (VPI).
- Copper Alloy Rotor Bars and End Rings.
- Class H Insulation.
- (VFD) Inverter Duty.
- 4532 Forged High-Strength Shaft.
- Single Shaft with Oilfield Hub.
- OPE Insulated Bearing.
- IP44 Enclosure
- Pressurized connection box (IP54) mounted on right or left side of motor as viewed from non-drive end, with bolt on cable connections and terminations for pressure sensor, thermostat, space heater, lockout switch & blower unit.
- Blower Assembly; 15HP, Explosion Proof, 3 Phase, 60 Hz, 460 Volts.
- (6) 100 Ohm Platinum RTD's (2) per phase.
- Pressure sensor, Explosion Proof.
- Lockout Switch, Explosion Proof.
- Space Heater, 120/240 Volt, Exponion Proof.
- Stub Shaft / Encoder Mount optional.
- Approx. Weight: 7,560 Lbs.

ENGINEERING DATA:

- Service Speed:
 - Belt drive: 0~2300 RPM (2300~3000 RPM: short time drive).
 - Direct Coupled: 0~3000 RPM (Continuous).
- Dielectric Test: 4025 V (900*2.25+2000, 900 V is inverter input Voltage).
- Permissible Vibration +/- 73.5 m/S² (+/-7.5G).
- Noise (@ No-Load): Approx. 91 dB(A) at 1m from motor frame.

<u>Rating:</u>	<u>Continuous:</u>	<u>Intermittent:</u>
Output (HP):	1230	1845
Output (KW):	918	1376
Voltage (V):	600	600
Current (A):	1170	1755
Speed (min-1):	800	800
Frequency (Hz.):	40.6	41.1
Efficiency (%):	94.7	92.9
Power Factor (%):	82.3	79.6
Slip (%):	1.18	2.33